Elpress mini

- electro-hydraulic crimping tool 6 to 70 mm²





Elpress AB · P.O. Box 186, SE-872 24 KRAMFORS, Sweden Tel: +46 (0)612-71 71 00 E-mail: sales@elpress.se | www.elpress.net

The Elpress mini tool PVL350 in a new sleek design with a high performance Li-Ion battery that streamlines your work with its improved battery capacity.

CHARACTERISTICS:

- Single-handed operation for easy control of all tool functions
- Slim fitting crimping head ideal for confined spaces
- High-performance 12 V Li-Ion battery with indication of charge status
- Opening, rotatable "flip-top" head for easy die change and good accessibility
- Easy and comfortable to use with one hand thanks to its ergonomic 2-component housing with grip-friendly protection
- Extremely lightweight and rapid crimping process for maximum efficiency
- Automatic return of dies when crimping is completed

TECHNICAL DATA PVL350:

Crimping force	35 kN
Crimping range	6-70 mm ²
Crimping process	about 3-4 s (dependent on material)
Number of crimps	about 180 for 70 mm² Cu
Battery voltage	12 V
Battery capacity	1.5 Ah, Li-Ion
Charge time	about 40 minutes.
Weight including battery	1.6 kg
Ambient temperature	-10°C to +40°C
Dimensions	330 x 85 x 60 mm

Elpress MINI – crimping dies

Applicati	on	Area	Dies	
CUT-connector		6-16 mm²	MB4016	
		KR/KRD, KS/KSD	KR/KRF, KS/KSF	KRT/KST
Hexagon	al 4-10 mm²	MB4016	MB4016	-
Hexagon	al 10 mm²	MB8	MB8	MB7
16 mm²	MB8	MB9	MB8,5	
	25 mm²	MB9	MB11	MB10
	35 mm²	MB11	MB13	MB12
	50 mm²	MB12	MB14,5	MB14
	70 mm²	MB14	MB17	MB16
	95 mm²	MB17		
		12-26 mm² (C6-10)	MBC5	
		30-50 mm² (C16-25)	MBC6	

