

# V600

- Hydraulic crimping head for Cu-terminals 10 - 240 mm<sup>2</sup> and C-sleeves up to 50/50 mm<sup>2</sup>

## V600



- is a part of Elpress 6 ton system
- has the same crimping dies as V611 and PVX611
- is used with Elpress pump PS710 or P4000

### Use:

For crimping of Cu-terminals of type KRF/KSF 10 – 150 mm<sup>2</sup>, KRD/KSD 10 - 185 mm<sup>2</sup> and KRT/KST 10 - 240 mm<sup>2</sup> and C-sleeves up to 50/50 mm<sup>2</sup>.

### Particulars:

- weight 2,1 kg
- dimensions 189 x 53 x 74 mm
- crimping force 55 kN
- robust textile bag with room for 10 die pairs

## Crimping dies for V600

For terminals / connectors

type KRF/KSF		type KRD/ KSD		type KRT/ KST	
areas, mm <sup>2</sup>	die pair	areas, mm <sup>2</sup>	die pair	areas, mm <sup>2</sup>	die pair
10 & 70	TB8-17	10/16 & 70	TB8-14	10&120	TB7-19
16 & 35	TB9-13	25&50	TB9-12	16&95	TB8,5-18
25 & 50	TB11-14,5	35&95	TB11-16	25&70	TB10-16
10 & 95	TB7-20	10&120	TB7-19	35&50	TB12-14
120	KB22	150	KB22	150	KB22
150	KB25	185	KB25	185	KB24
				240	KB26

branch sleeves type C

areas, mm <sup>2</sup>	die pair
6-10/6-16 + 6-25/16-25	TBC5-C6
6-50/50 + 16-50/35-50 + 25-50/25-50	TBC89-B13



Elpress is environmental and quality certified according to ISO 14001 and ISO9001.

